

DIGITUS® USB-C adapter, USB A - USB-C

AK-300524-000-S
EAN 4016032467410



USB Type-C adapter, type A to C M/F, 3A, 5GB, 3.0 Version, bl

The DIGITUS® USB Type A to USB-C adapter allows you to use your current USB Type-C devices on an older USB A port. The adapter supports the USB 3.0 specification with data transfers of up to 5Gbps and provides a maximum power of 15 W (3 A). By simply reversing the USB-C connector, you can switch between USB 3.0 and USB 2.0 speeds, provided they are supported by the USB A port. The integrated 56k pull-up resistor protects your devices from damage due to overloading and only supplies as much power as the connected USB-C device requires. Backwards compatible with the USB 2.0 / 1.1 standards, this adapter allows you to use the full bandwidth of previous USB versions.

Connect USB-C devices with a USB A port - Continue to use your devices with a USB A port

- Adapter: From USB A to USB-C (use USB-C devices on USB A ports)
- SuperSpeed data transfer: 5 Gbit/s (USB 3.0 if supported by USB A)
- USB-C power supply: 3A max. (15 W)
- USB Type-C plug: can be used on both sides, reverse polarity protected
- Integrated 56k pull-up resistor to protect your source devices (notebook, PC)

- Downwards compatible with USB 2.0 / 1.1
- Operating temperature: -15 ~ 50°C
- Operating humidity: -25 ~ 80% RH (non-condensing)
- Storage temperature: -20 ~ 60°C
- Storage humidity: 20% ~ 85% RH (non-condensing)
- Housing material: Aluminum
- Color: Black

Attributes

- Color cable: black
- Connector 1: USB A, plug
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Length: 0.04 m
- Shielding: Unshielded
- USB-C Products: yes

Package contents

- 1 x USB Type-C adapter, USB A - USB-C
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	5.00	26.00	38.00	24.00	23.71
Packaging Unit Inside	1	0.01	3.00	20.00	25.00	1.50
Packaging Unit Single	1	0.01	0.70	9.00	20.00	126.00
Net single without Packaging	0	0.01	0.64	1.40	3.80	3.40

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com