DIGITUS Dual Design Monitor Clamp Mount with 2 x USB & Gas Spring

DA-90417 EAN 4016032475057



Dual Gas Spring Monitor Clamp Mount 17-32",2x9 kg max, space grey

The dual designer monitor arm solution with integrated USB connections unites ergonomics and connectivity. Users benefit from a perfectly ergonomically adapted monitor position and can also use their mobile devices such as smartphones, tablets or USB sticks via the integrated USB port. The monitor arm supports displays with a screen diagonal from 17" to 32" (VESA 75 / 100) up to a maximum load of 9 kg per monitor arm. The integrated gas springs with spring tension meter and quick-release function make it easier for you to position and clip in the monitor. The swiveling of the monitor arm can be reduced to 180° to prevent collisions with walls or other obstacles. You can access the USB connectivity and the ergonomic advantages of the adjustable monitor bracket from DIGITUS®.

Ergonomics combined with stylish design and practical USB connectivity

- Monitor bracket:
- Suitable for monitors with dimensions between 17" and 32", also suitable for curved displays
- Maximum load capacity: 2 9 kg per monitor
- Quick release function: Simple clipping in of the monitor to the mount
- Swivel the mount by up to 360° (with rotational stop feature, adjustable to 360°/180°)



- Inclination of the VESA bracket: -40° to +40°
- Rotation of the VESA bracket: -180° to +180°
- Supported VESA dimensions: 75x75, 100x100
- Maximum height adjustment: 44.3 cm
- For tabletop thicknesses between: 10 85 mm
- Material: Steel, aluminum, plastic
- Dimensions: W 107 x D 12.2 x H 63 cm
- Weight: 5.4 kg
- Color: Space gray
- USB connections:
- 2 x USB A (Extension: Can be connected with PC or notebook outputs)

Attributes

- Monitor weight (max.): 9 kg
- Mounting method: Clamp-mount
- Number of monitors: 2
- Size of monitors: up to 32"
- VESA mount: 75x75 mm, 100x100 mm
- VESA mount: 75x75 mm, 100x100 mm

Package contents


- 1 x Dual Designer Monitor Bracket with 2 x USB, gas spring and clamp mount
- 2 x USB 3.0 connecting cable, x m
 - 1 x Mounting material
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3	19.86	35.50	46.00	40.50	66,136.50
Packaging Unit Inside	1	6.62	0.00	0.00	0.00	0.00
Packaging Unit Single	1	6.62	33.60	44.50	12.70	18,989.00
Net single without Packaging	0	5.44	12.20	107.00	63.00	82,240.20

1



More images:



Safety notes

- Please read the entire manual before starting assembly and installation. Please contact your local dealer if you have any questions about the instructions or warnings.
- · CAUTION: Use with products that exceed the permitted weight may result in damage or possible injury.
- Brackets should be fitted in accordance with the installation instructions. Incorrect installation can result in damage or injury.
- Use safety equipment and suitable tools. The product should only be installed by specialists.
- This product can be installed on timber-framed, solid concrete or stone walls.
- The load-bearing surfaces should be able to safely withstand the entire weight of appliances and all additional components.
- Only use the installation screws supplied and DO NOT TIGHTEN the screws TOO TIGHT.
- This product contains small parts that can cause a choking hazard if swallowed. Keep these parts away from children.
- Only use this product indoors. Using the product outdoors can lead to injuries and damage.



- IMPORTANT: Before installation, please compare all components received with the components list. If parts are damaged or missing, ask your local dealer for replacement parts.
- MAINTENANCE: Check the bracket regularly for safety and stability (preferably every three months).

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com