

DIGITUS USB-3.0 Gen.1, USB Type-C extension cable; M/F

DB-300230-005-S
EAN 4016032481171



USB-C/M to USB-C/F PD60W Gen1 USB3.0 Extension Cable 0.5m 4K@60Hz, bi

The DIGITUS® USB 3.0 Gen. 1 extension cable is an all-rounder among cables. Thanks to the Thunderbolt 3 protocol, it can be used for PCI Express, DisplayPort and Host-to-Host transfers. With this cable, you can transfer audio/video signals, data as well as power. The data transfer speed is 5 Gbit/s. This allows you to transfer large quantities of data such as films and music within seconds. Video signals are transmitted max. in 4K with a display refresh rate of 60 Hz. Thanks to USB Power Delivery, the charging function is ensured. With the corresponding charging device, you can charge your smart devices rapidly with max. 60 W (3 A / 20 V). The USB Type-C interface enables wide compatibility with devices with this connection.

Supports the following transmission types: audio/video data transfer/charging function

- Supports: 4K @ 60Hz
- Supports data transfer rates of up to 5 Gbit/s
- Backwards-compatible with Thunderbolt 3 and USB 2.0
- Supports USB Power Delivery with 20 V, 3A and 60W
- Strand material: CU
- Connection 1: USB Type-C plug
- Connection 2: USB Type-C jack
- Dimensions plug 1: 25*11mm
- Dimensions plug 2: 18.5*11mm
- Color of connections: Gray
- Contact material: nickel-plated
- Contact surface: nickel-plated

- Cable color: black
- Length: 0.5
- USB-C products: yes
- OD: 4.3 mm
- Material: TPE
- Operating temperature: -20 °C to +60 °C
- Storage temperature: -10 °C to +50 °C
- Humidity: 95%
- Bending radius: 60
- Tensile strength: 4 kg/min
- Manufacturer's notice:
- If you connect a USB-C monitor/TV/projector to a PC equipped with USB Type-C, make sure that your USB-C display supports DisplayPort signal output.
- The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB-C jack
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Length: 0.5 m

Package contents

- 1x USB-3.0 Gen.1, USB Type-C extension cable; M/F (0.5m)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	90	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.04	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.02	0.00	0.00	0.00	0.00

More images:

