

DIGITUS® Socket Strip with Aluminum Profile, 10-way, 2 m cable IEC C20 plug

DN-95427

EAN 4016032483533



1U Aluminum PDU, rackmountable, 8 x C13, 2 x C19 16A, 230VAC, 50/60Hz, IEC C20 plug

The DIGITUS® socket strips are the perfect solution for your network or server cabinet. With regard to current distribution, the PDU fulfills the requirements of many applications in IT, network technology and laboratories. The PDU can be used ideally with your input connector IEC60320 C13 and C19 as additional 19" distribution for UPS. The individual C13 and C19 outputs are equipped with extraction protection.

Safe and professional current supply in the 19" range

- Extraction protection at each output (for C13 and C19 standard cables)
- Horizontal 19" installation in the rack
- Housing: Aluminum profile
- Plastic components made of ABS UL-94V-0
- Input: Plug IEC60320 C20, 230 Vac / 16 A
- Output: Device sockets 8 x IEC60320 C13, 2 x IEC60320 C19, extraction protection integrated for every output

- Cable: Cable cross section: 1.5 mm², length: 2 m
- Dimensions: 482.6 (19") x 45 (1U) x 60 mm (HxWxD)

Attributes







- Current: 16 A
- Input Plug: IEC 60320 C20 inlet
- Installation: Rack 1U
- Outlets: IEC 60320 C13, IEC 60320 C19
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Package contents

- Scope of delivery: 1 socket strip, 2 mounting brackets; 1 safety instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	8.50	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.85	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.85	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	933.15

More images:



Safety notes

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com