

# DIGITUS® USB-C - DisplayPort adapter cable, 8K / 30 Hz

DB-300334-010-S  
EAN 4016032484264



**8K@30Hz. USB Type C to DP, adapter cable HBR3, Aluminum Housing, Black 1m**

The DIGITUS® USB Type C DisplayPort adapter cable supports the transfer from a USB Type C source to a DisplayPort interface. For example, you can connect your laptop (USB Type-C equipped) to your monitor, TV or projector (DisplayPort interface). Power is supplied via the USB port, so no external power source is required.

**The DIGITUS® USB Type-C to DisplayPort adapter cable supports the transfer of USB Type-C sources to DP-capable displays.**

- Supports: Resolutions up to 8K (7680x4320) at a refresh rate of 30Hz.
- Supports: Resolutions up to 4K at 144Hz
- Supports: Resolutions up to 2K at 165Hz
- Transmission speed: 25.92 Gbit/s
- Supports the transmission of audio and video signals
- Aluminum housing
- Ferrite filter: none
- USB-C products: yes
- Copper cores, foil and braid shielded for robustness and a reliable connection
- DisplayPort Standard: DP 1.4
- USB standard: USB4 Gen2 20Gbps

- Supported: Multi-Stream Transport (MST)
- Manufacturer's instructions:
- If you connect a USB-C monitor/TV/projector to a DP-equipped PC, please make sure that your USB-C display supports DisplayPort signal output.
- The video output capability depends on the graphics card of your notebook and the connected monitor. Some monitors also limit the available resolution.
- AOC - Active optical cable: no

**Attributes**

- AWG: 34
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: DP, plug
- Connector surface: gold-plated
- Ferrite filter: none
- USB compliance: USB 4.0
- Length: 1 m
- Shielding: triple shielding

**Package contents**

- 1x USB Type-C adapter cable, USB Type-C to DP, 1m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	4.20	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.04	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.04	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	210.60

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)