

DIGITUS 8-Port Gigabit PoE Networkswitch, 19 Zoll, unmanaged, 2 Uplinkports, SFP, 140 W, af/at

DN-95341-1 EAN 4016032484738





8 Port GE 2 SFP Uplink PoE Switch POE at, 150 W Powerbudget

The DIGITUS 8-Port Gigabit Rack mount Switch with eight Power over Ethernet ports and two additional SFP Fiber Port, offers your network significant improvement in terms of performance and efficiency. Thanks to PoE support, you only need a single (network) cable for power and data transfer. This switch makes it much easier to connect devices such as access points, network cameras, and IP telephones, and requires far less cabling than alternatives. It also allows you to extend your network in places where there are no power supply cables or sockets available. The switch does not require any configuration and therefore guarantees quick and seamless integration into the network. Moreover, the switch has a rack mountable design and can be easily installed with many standard racks, which makes this device the perfect solution for data center and local server rooms.

Thanks to the PoE function, no additional power supply unit is required for the connected devices Minimize cabling for wireless APs, IP telephones, and any other PoE capable device

- 8-Port 10/100/1000 Mbps PoE Gigabit rack mountable Switch + 2x SFP Uplink
- Ethernet IEEE802.3 / 802.3u / 802.3x/802.3ab/802.3z / IEEE802.3 af/ at
- Power over Ethernet (PoE) You only need one cable for power and data transfer
- PoE power budget: 140 Watts
- Supports PoE: Provides 8 PoE Port, each port output 30W maximum power
- No configuration necessary
- Status LEDs on each port

- Pin Feet: V+ (RJ45 Pin 3, 6) V- (RJ45 Pin 1, 2)
- Backplane: 20Gbps
- MAC address table: 4K
- Rack mountable in system rack (1U)
- Internal power supply: 150W
- Dimensions (L x W x H): 275 mm x 200 mm x 44 mm
- Weight: 4500g
- Ethernet speed: Gigabit
- Number of ports (uplink): 2
- Connection of uplink port: SFP VLAN: no
- PoE standard: IEEE802.3at (PoE+)
- Attributes
- Number of ports: 8
- PoE Power budget: 140 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Industrial usage: no
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vanadlism: no
 - Uplink port connection: SFP
- VLAN: no

Package contents

- 8 port PoE switch +2 SFP uplink ports
- Net

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	13.86	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	2.77	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.77	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	3.97

More images:









Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- · Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- · Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- · Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and return it to an authorized service centre for repair
- The mains cable, power supply unit or plug for the power supply is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com