

DIGITUS 11-Port USB-C Dock, grey, 2x HDMI, VGA

DA-70898

EAN 4016032490371



11-Port USB-C Dock, grey, 2x HDMI, VGA USB-C, 3x USB-A, RJ45, 1x 3.5mm, SD/MicroSD

The multifunctional DIGITUS® docking station has everything you need to create a fully equipped workplace. Via the 2x HDMI® and VGA port, you can extend your desktop to 3 additional monitors or connect projectors / TV devices. In combination with your existing screen, this allows you to clone your desktop on up to 4 displays or extend on up to 3 displays. Additionally, the docking station is equipped with a USB-C™ port which features Power Delivery (PD). This allows you to charge your connected notebook / tablet while in use. Three additional USB ports provide you with plenty of space to connect additional mobile devices, which can be charged while in use. Of course, other USB peripheral devices such as a mouse or keyboard can also be connected using the 3 USB 3.0 ports. Two card readers for SD/TF cards and MicroSD cards are also integrated, as a Gigabit Ethernet Port. This allows you to connect your notebook to the local network or Internet via the docking station using a network cable. The Desktop-Multi-Tool features are rounded off with a stereo audio jack. This allows you to use a microphone, speaker, or headset. With the multifunctional DIGITUS® docking station, you can extend your notebook, tablet or smartphone with just one USB-C™ port.

The DIGITUS® USB-C™ docking station extends your notebook or tablet by 11 additional connections

- 2 x HDMI® connection: 4K/30 Hz (3840 x 2160p)
- 1 x VGA connection: Full HD (1920 x 1080, 60 Hz)
- Triple display support - connect up to 3 displays simultaneously
- Supports SST and MST Mode (Single Stream Transport mode / Multi Stream Transport mode)
- Three simultaneous video output signals - resolution: SST / MST mode max. 1080p/60 Hz
- 1 x USB-C™ plug: Connection with the host (notebook, tablet)
- 1 x USB-C™ connection: Power Delivery 3.0 (100 W max.)
- 3 x USB 3.0 connection: 5 Gbps, 4.5 W (5 V / 0.9 A)
- 1 x SD card reader: 480 Mbps

- 1 x MicroSD card reader: 480 Mbps
- 1 x Gigabit Ethernet interface: 10/100/1000 Mbps
- 1 x audio connection: 3.5 mm stereo (stereo-audio, microphone)
- Plug and Play - no driver or app installation required
- Operating systems: Windows 10/8/7 macOS® 9.X & 10.X, Linux, ChromeOS, Android, iOS®
- Operating temperature: -40°C ~ 80°C
- Connection cable length: 20 cm
- Housing: Zinc plating with silicone surface
- Dimensions: L 28 x B 8 x H 1,8cm
- Weight: 286 g
- Color: silver
- Manufacturer's notice:
- Not all USB-C™ ports support all functions of the USB Type-C™ standard. Make sure that your notebook's USB-C™ port supports the DisplayPort Alternate Mode (DP Alt Mode) as well as USB Power Delivery (PD).

Attributes

- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- Housing: Aluminum
- LAN connector (RJ45): yes
- USB-C Power Delivery: 100W
- Card reader: yes
- Number of audio ports: 1
- Number of display ports: 3
- Number of network ports: 1
- Number of USB A ports: 3
- Number of USB-C ports: 1
- Number of video ports: 3
- Video connection ports: HDMI, VGA

Package contents

- USB-C™ Docking Station, 12-Port
- QIG

Logistics

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|------------------------------|--------------|-------------|------------|------------|-------------|-------|
| Packaging Unit Carton | 1 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Inside | 1 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.25 | 0.00 | 0.00 | 0.00 | 0.00 |
| Net single without Packaging | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 23.40 |

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com