

# DIGITUS® Front panel and mounting frame for multimedia / Keystone modules

DN-93831-B

EAN 4016032507376



**Wallplate for Keystone Jacks, black 80x80 frame, 50x50 central plate, design comp.**

The DIGITUS® junction box is suitable for the installation of shielded DIGITUS® Keystone modules. Integrated dust protection flaps ensure optimum protection. The angled outlet for connecting the module is 45° vertical. The junction box is fully design-compatible with standard switch ranges.

- Keystone mount version: 45° outlet
- Areas of application: Cavity wall box, sill channel, surface-mounted housing
- Standards: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for installation in trunking, flush-mounted & surface-mounted

- Central earthing connection
- Integrated dust protection flap
- Plastic labeling field
- Design-compatible with the standard switch ranges of switch manufacturers
- Technical features:
  - Material empty housing: die-cast metal
  - Material central plate: ABS UL 94V-0
  - Frame material: ABS UL 94V-0
- Physical properties:
  - Operating temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
  - Can be used as a 1-port and 2-port data socket
  - Color: Black RAL 9005

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	172.80

**More images:**



**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)