

PURELINK Purelink PureInstall PI1100

PI1100-050
EAN 4260134119337



Our Pure Install Series for high claim offers guaranteed and certified PureLink® quality at an excellent price / performance ratio. High-quality materials and the most suitable connectors and couplings, gold plated contacts and the elimination of all unnecessary make this PureLink® products to a good investment anywhere the work takes place. For maximum flexibility, including the Pure Install series alongside high-quality cables, adapters, signal amplifier also versatile, Wall Plates and other installation accessories. Through best quality from a single source, you can be sure that everything fits together perfectly. Connections: plug material PVC Contact material 24 carat gold-plated shielding Yes connection 1 HDMI Type A connector (19pin) dimensions A.1 43.5 x 19.5 x 10.5 (mm) connection 2 HDMI Type A socket (19pin) dimensions A.2 39.6 x 23.6 x 12.3 (mm) contacts 24 carat gold-plated, durable design Electric wire: Type round cable length 1.0 m | 2.0m | 3.0m | 5.0m Inner conductor material Tinned copper OFC AWG AWG28 number of shieldings 3 times screening 1 Aluminum foil (100% leak) shielding 2 Aluminum foil (100% leak) shielding 3 Braid (100% leak)Material outer sheath Highly elastic PVC

Outer sheath diameter 7.3mm Signal transmission: Supported standards HDMI transmission modes Digital audio and video signals Max. Bandwidth 340 MHz Transmission rate max. 10.2 Gbit / s Resolution max. 4K (4096x2160) Supported color spaces 16/24 bit RGB / YUV, Deep Color, xvColor™ Supported audio standards Audio Return Channel (ARC), Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™, DVD Audio, SA-CD More standards HDMI Ethernet Channel (HEC), 3D, HDCP, CEC, 4K2K (2160i / p), full HD (1080i / p), HD ready (720i / p), SDTV (480i / p)

- High Speed HDMI for 3D and HDTV resolutions up to 4k (2160p)
- Integrated Ethernet Channel for 100 MBit Network transmission via HDMI
- High purity OFC tinned copper wire and 3-shielding for optimum transmission quality
- Innovative Secure Lock System™ for HDMI connections
- Especially suitable for professional applications and installations
- AOC - Active Optical Cable: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.33	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.33	0.00	0.00	0.00	0.00