

PURELINK Purelink PureInstall - High Speed HDMI DVI Kabel

PI3000-075
EAN 4260134120128



Our PureInstall Series for high claim offers guaranteed and certified PureLink® quality at an excellent price / performance ratio. High-quality materials and the most suitable connectors and couplings, gold plated contacts and the elimination of all unnecessary make these PureLink® products to a good investment anywhere the work takes place. For maximum flexibility, including the Pure Install series alongside high-quality cables, adapters, signal amplifier also versatile, Wall Plates and other installation accessories. Through best quality from a single source, you can be sure that everything fits together perfectly. connections plug material PVC Contact material 24 carat gold-plated shielding Yes connection 1 HDMI Type A connector (19pin) dimensions A.1 43.5 x 19.5 x 10.5 (mm) connection 2 DVI-D connector (18 + 1pin) dimensions A.2 47.7 x 37.7 x 15.8 (mm) contacts 24 carat gold-plated, durable design Electric wire Type round cable length 0.5 m | 1,00m | 1.5 m | 2.00m | 3,00m | 5,00m | 7.5 m | 10,0m | 15.0m Inner conductor material High purity, tinned copper OFC AWG AWG28 to 5m | AWG24 from 7,50m number of shieldings 3

times screening 1 Aluminum foil (100% leak) shielding 2 Aluminum foil (100% leak) shielding 3 Braid (100% leak) Material outer sheath Highly elastic PVC Outer sheath diameter 7.3mm to 5m | 10.5mm from 7,50m signal transmission Supported standards HDMI, DVI transmission modes Digital video signals Max. Bandwidth 165 MHz Transmission rate max. 3.72 Gbit / s Resolution max. WUXGA (1920x1200) Supported color spaces 8 bit RGB / YUV, Deep Color, xvColor™ More standards HDCP, CEC, full HD (1080i / p), HD ready (720i / p), SDTV (480i / p)

- High-speed connection for HDTV resolutions up to WUXGA (1920x1200) and Full HD (1920x1080)
- High purity OFC tinned copper wire and 3-shielding for optimum transmission quality
- Innovative Secure Lock System™ for HDMI connections
- Especially suitable for professional applications and installations
- AOC - Active Optical Cable: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	12	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.98	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.98	0.00	0.00	0.00	0.00