

Planet Industrial Fast Ethernet Switch, 4 Port RJ45 + 2 Port SC

PL-ISW-621TS15
EAN 4711213686535



Planet IP-30 Industrieswitch 4x10/100 RJ45,1x100-FX SC

Industrial switch, IP 30, aluminum casing, 4x 10/100Base-TX (RJ45) to 2x 100Base-FX (SC, SM-15KM), IP-30 Aluminium Industry, Auto MDI / MDI-X, half / full duplex, Supports 6KV DC Ethernet ESD protection, Supports 6KV DC EFT protection for power line, operating temperature -40 - 75 degrees C, for DIN- rail and wall mounting, Dimension (W x D x H) 135 x 87 x 32 mm, power supply for 12 - 48V DC

The best Solution for rough Environmental Conditions!

- 4-Port 10/100Mbps Auto MDI/MDI-X RJ45
- 2-Port 100Base-FX interface for up to 15km (Single-mode fiber 9/125µm) transmission distance
- Complies with IEEE 802.3, IEEE 802.3u 10/100Base-TX, 100Base-FX Ethernet standard
- Supports Auto-Negotiation and 10/100Mbps half / full duplex mode for each copper port
- High performance Store and Forward architecture
- Prevents packet loss with back pressure (Half-Duplex) and IEEE 802.3x PAUSE frame flow control (Full-Duplex)

- 1.2Gbps Backplane
- Integrated address look-up engine, supports 2K absolute MAC addresses
- 1Mbit on-chip frame buffer
- IP-30 protection with metal case
- Suitable for DIN rail (top-hat rail) mounting
- Redundant Power Design: 12~48V DC redundant power with polarity reverse protect function
- -40 to 75 °C operating temperature
- Number of ports: 4
- Ethernet speed: Fast Ethernet
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	11.50	32.00	41.00	29.00	38.00
Packaging Unit Inside	1	0.64	5.00	21.00	15.00	1.60
Packaging Unit Single	1	0.64	5.00	21.00	15.00	1.60
Net single without Packaging	0	0.64	0.00	0.00	0.00	0.00

More images:

