

# Noctua NH-D15 premium Cooler

**NOC-NH-D15**  
**EAN 4716123315360**



Built on the basis of the legendary NH-D14 and carrying on its quest for ultimate quiet cooling performance, Noctua's flagship model NH-D15 is an elite-class dual tower cooler for the highest demands. Its expanded heatpipe layout and two premium grade NF-A15 140mm fans with PWM support for automatic speed control allow it to further improve the NH-D14's award-winning efficiency. Topped off with the trusted, pro-grade SecuFirm2™ multi-socket mounting system, Noctua's proven NT-H1 thermal compound and full 6 years manufacturer's warranty, the NH-D15 forms a complete premium quality solution that represents a deluxe choice for overclockers and silent-enthusiasts alike. Fan specifications Model: 2x Noctua NF-A15 PWM Bearing: SSO2 Max. Rotational Speed (+/- 10%): 1500 RPM Max. Rotational Speed with L.N.A. (+/- 10%): 1200 RPM Min. Rotational Speed (PWM, +/-20%): 300 RPM Max. Airflow: 140,2 m³/h Max. Airflow with L.N.A.: 115,5 m³/h Max. Acoustical Noise: 24,6 dB(A) Max. Acoustical Noise with L.N.A.: 19,2 dB(A) Input Power: 1,56 W Voltage Range: 12 V MTBF > 150.000 h

- Socket compatibility Intel LGA2011 (Square ILM), LGA1156, LGA1155, LGA1150 & AMD AM2, AM2+, AM3, AM3+, FM1, FM2, FM2+ (backplate required)

- Height (without fan): 160 mm
- Width (without fan): 150 mm
- Depth (without fan): 135 mm
- Height (with fan): 165 mm
- Width (with fan): 150 mm
- Depth (with fan): 161 mm
- Weight (without fan): 1000 g
- Weight (with fan): 1320 g
- Material Copper (base and heat-pipes), aluminium (cooling fins), soldered joints & nickel plating
- Fan compatibility: 140x150x25 (with 120mm mounting holes), 140x140x25 (with 120mm mounting holes), 120x120x25

## Package contents

- 2x NF-A15 PWM premium fan
- 2x Low-Noise Adaptor (L.N.A.)
- Y-cable
- NT-H1 high-grade thermal compound
- SecuFirm2™ Mounting Kit
- Noctua Metal Case-Badge

## More images:

