

NOCTUA

NOC-NFA14IPPC3000PWM
EAN 4716123315452



Noctua NF-A14 industrialPPC-3000 PWM Conceived for industrial heavy duty applications that require enhanced cooling performance and advanced ingress protection, the NF-A14 industrialPPC (Protected Performance Cooling) is a ruggedised high-speed version of the award-winning retail model. Thanks to the outstanding aerodynamic efficiency of the NF-A14 design and the use of a novel three-phase motor, the industrialPPC version provides superior airflow and pressure capacity while keeping noise levels and power consumption moderate as against comparable high-speed fans. While its fibre-glass reinforced polyamide construction and certified water and dust protection make the NF-A14 industrialPPC suitable for operation in challenging environments, the renowned SSO2 bearing technology guarantees an MTBF of over 150.000hrs. Topped off with Noctua's trusted reliability and 6 years manufacturer's warranty, the NF-A14 industrialPPC is an ideal choice for highly demanding applications that require superior flow rates and ultimate dependability. Scope of Delivery: Fan 4 Fan Screws

- Size: 140x140x25 mm
- Connector: 4-pin PWM
- Bearing: SSO2
- Blade Geometry: A-Series with Flow Acceleration Channels
- Frame Technology: AAO (Advanced Acoustic Optimisation)
- Rotational Speed (+/- 10%): 3000 RPM
- Min. Rotational Speed (PWM +/-20%): 800 RPM
- Airflow: 269,3 m³/h
- Acoustical Noise: 41,3dB(A)
- Static Pressure: 10,52 mm H2O
- Max. Input Power: 6,6 W
- Max. Input Current: 0,55 A
- Voltage: 12 V
- MTBF: > 150.000 h
- Ingress Protection: IP52
- Material: Fibre-glass reinforced polyamide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.31	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.31	0.00	0.00	0.00	0.00

More images:



