

TP-Link AP Wi-Fi 6 1x2GB 1xGB Indoor 2.4Ghz:574Mbps/ 5Ghz:2402Mbps

DECO-X50-POE-3P
EAN 4897098687918



The access points of the TP-Link DECO series, with their minimalist, modern design, are particularly suitable for private environments. They are capable to be mounted on ceilings and walls or make a good figure standing. The integrated MESH function allows the devices to be easily connected to each other wirelessly, if wiring is not possible. The DECO x50 PoE access points can be powered either by the included power brick or via PoE (802.3at) through the 2.5Gbps network interface. Additionally, a 1Gbps RJ45 interface is installed to connection other network devices direct.

- AX3000 Dual Band Wi-Fi – 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Easy installation on wall or ceiling using mounting plate
- AI supported MESH environment for better range and latency

- Network connections with 1x 2.5Gbps and 1x 1Gbps
- Powered by included power brick or through PoE (802.3at)
- 2x2 MU-MIMO
- Mode: Router or Access Point
- Operating temperature: 0°C ~ 40°C / Humidity: 10% ~ 90%RH
- Storage temperature: 0°C ~ 60°C / Humidity: 5% ~ 90%RH

Package contents

- 3x DECO x50 PoE
- 1x RJ45 network cable
- 3x power brick
- 1x mounting kit
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	4	11.32	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	2.83	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.83	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	140.80

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH

Am Trippelsberg 100

Düsseldorf, Germany

<https://www.tp-link.com/de/>

support.de@tp-link.com