

TP-Link Omada 24-Port Gigabit-Stackable Lite L3 Managed PoE++ Switch with 4× 10G Slots

SG5428XMPP
EAN 8885020626445



Omada SG5428XMPP is a reliable, entry-level L3 managed PoE++ switch tailored for the access layer, offering L3 routing, fast 10 Gbps cable speeds, and stacking options. It has a PoE budget of 500W, 24× Gigabit RJ45 ports (8× PoE++, 16× PoE+), 4× 10 Gbps SFP+ slots, physical stacking capability, and centralized management. Integrated with strong security and extensive management features, the SG5428XMPP provides a reliable network solution for SMBs and ISPs.

24× Gigabit RJ45 ports and 4× 10 Gbps SFP+ slots provide up to 128 Gbps per unit switching capacity. Up to 4 physical stacking units strengthen the network fabric with built-in redundancy and performance.

- 24× 10/100/1000 Mbps RJ45 ports (8× PoE++, 16× PoE+)
- 4× 1/10 Gbps SFP+ slots
- Rackmountable
- Maximum power consumption: 587.7 W (220V/50Hz) (connected to 500 W PD @ 25 °C)

- Maximum Heat Dissipation: 2004.06 BTU/hr (220V/50Hz) (connected to 500W PD @ 25°C)

Attributes

- Industrial usage: no
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: no

Package contents

- SG5428XMPP
- Power cord
- Console cable
- Rackmount Kits
- Rubber feet
- Short installation guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3	18.03	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	2,390.85

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH
Am Trippelsberg 100
Düsseldorf, Germany
<https://www.tp-link.com/de/>
support.de@tp-link.com