

TP-Link Omada AX3000 Gigabit Desktop DSL Gateway

DR3650V

EAN 8885020626759



Omada AX3000 Gigabit Desktop DSL Gateway PORT: 1 × Gigabit WAN/LAN port, 4 × Gigabit LAN ports, 1 × DSL port, 2 × FXS ports, 2 × USB 3.0 ports SPEED: 574 Mbps at 2.4 GHz + 2402 Mbps at 5 GHz (HE160) Wi-Fi speed, VDSL profile 35b 350/60 Mbps FEATURE: Integration with Omada SDN Controller, Omada APP, Support for SSL VPN, OpenVPN and Wireguard/IPsec/PPTP/L2TP/L2TP over IPsec VPN, 3 × detachable antennas, 160MHz supported, OFDMA, MU-MIMO, Beamforming, Load Balance, Link Backup, Policy-based Firewall, Static Routing, Policy Routing, Multi-net DHCP, VLAN, Stateful ACL, mDNS Repeater, Bridge VLAN, VoIP, TR-069

Omada AX3000 Gigabit Desktop DSL Gateway

- 3 × RJ11 ports (2 × FXS, 1 × DSL)
- 5 × RJ45 Gigabit ports (1 × WAN/LAN port, 4 × LAN ports)

- 2 × USB 3.0 ports
- Signal rate: 2.4 GHz: 574 Mbps; 5 GHz: 2402 Mbps (HE160)
- Power supply: 12V DC / 3.3A power supply
- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Storage Temperature: -40°F to 158°F (-40°C to 70°C)

Package contents

- DR3650v
- Short installation guide
- Power supply
- Ethernet cable
- Telephone cable
- Rubber feet

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	6	10.74	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	24.00

More images:





EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH
Am Trippelsberg 100
Düsseldorf, Germany
<https://www.tp-link.com/de/>
support.de@tp-link.com