

TP-Link Omada AX3000 Wi-Fi 6 Gigabit Desktop DSL Gateway

DR3650V-4G
EAN 8885020626773



Omada 4G+ Cat6 AX3000 Gigabit Desktop DSL Gateway PORT: 1 × Gigabit WAN/LAN port, 4× Gigabit LAN ports, 1 × DSL port, 2×FXS ports, 1× USB 3.0 port, 2 nano-SIM slots (4G+ Cat6) SPEED: 574 Mbps at 2.4 GHz + 2402 Mbps at 5 GHz (HE160) Wi-Fi speed, VDSL profile 35b 350/60 Mbps, 300 Mbps Download LTE speed FEATURE: Centralized management by Omada SDN Controller, Omada app, support for SSL VPN, OpenVPN, and Wireguard/IPsec/PPTP/L2TP/L2TP over IPsec VPN, 4G+ Cat6 LTE, 2× detachable LTE antennas, 3× detachable Wi-Fi antennas, 160MHz supported, OFDMA, MU-MIMO, beamforming, load balancing, link backup, policy-based firewall, static routing, policy routing, multi-net DHCP, VLAN, stateful ACL, mDNS repeater, bridge VLAN, VoIP, TR-069

Omada AX3000 Wi-Fi 6 Gigabit Desktop DSL Gateway

- 1× Gigabit WAN/LAN port
- 4× Gigabit LAN ports
- 1× DSL port

- 2× FXS Ports
- 1× USB 3.0 (supports USB LTE dongle and USB memory)
- Dual Nano SIM Slot (4G+ Cat6)
- Signal rate: 2.4 GHz: 574 Mbps; 5 GHz: 2402 Mbps (HE160)
- Power supply: 12V DC / 3.3A power supply
- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Storage Temperature: -40°F to 158°F (-40°C to 70°C)

Package contents

- DR3650v-4G
- Short installation guide
- Power supply
- Ethernet cable
- Telephone cable
- Rubber feet
- SIM Card Eject Pin

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	6	9.90	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	24.00

More images:





EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH
Am Trippelsberg 100
Düsseldorf, Germany
<https://www.tp-link.com/de/>
support.de@tp-link.com