

TP-Link Omada 4G+ Cat6 AX3000 Gigabit VPN Gateway with 4-Port PoE+

ER706WP-4G
EAN 8885020627428



Omada 4G+ Cat6 AX3000 Gigabit VPN Gateway with 4-Port PoE+ PORT: 1× Gigabit SFP WAN/LAN port, 1× Gigabit RJ45 WAN port, 4× Gigabit WAN/LAN RJ45 ports, 2 Nano SIM slots (4G+ Cat6) SPECIFICATION: 802.3 at/af, 4 ports with 45W PoE power, desktop and wall-mounted steel chassis SPEED: 574 Mbps at 2.4 GHz + 2402 Mbps at 5 GHz (HE160) Wi-Fi speed, 300 Mbps download LTE speed FUNCTION: Centralized management by Omada SDN Controller, Omada App, Omada APP, support for SSL VPN, OpenVPN and Wireguard/IPsec/PPTP/ L2TP/L2TP over IPSec VPN, 4G+ Cat6 LTE, 2× detachable LTE antennas, 3× detachable Wi-Fi antennas, 160MHz supported, OFDMA, MU-MIMO, Beamforming, Load Balance, Link Backup, Policy-based Firewall, Static Routing, Policy Routing, Multi-net DHCP, VLAN, Stateful ACL, mDNS Repeater, Bridge VLAN

Omada 4G+ Cat6 AX3000 Gigabit VPN Gateway with 4-Port PoE+

- EU LTE band: 4G LTE-FDD: B1/B3/B5/B7/B8/B20/B28/B32 (2100/1800/850/2600/900/800/700/1450 MHz); 4G LTE-TDD: B38/B40/B41 (2600/2300/2500MHz); 3G DC-HSDPA/HSPA+/HSDPA/HSUPA/WCDMA: B1/B3/B5/B8 (2100/1800/850/900 MHz)

- SIM Type: 2× Nano SIM Slots (4G+ Cat6)
- Frequency: Downlink: 300 Mbps; Uplink: 50 Mbps
- 1× Gigabit SFP WAN/LAN port
- 1× Gigabit WAN port; 4× Gigabit WAN/LAN ports
- Signal rate: 2.4 GHz: 574 Mbps; 5 GHz: 2402 Mbps (HE160)
- PoE ports: 4× PoE+ output, 45W PoE budget
- Maximum Power Consumption: 64.9W with PoE Max; 19.8W without PoE
- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Storage Temperature: -40°F to 158°F (-40°C to 70°C)

Package contents

- ER706WP-4G
- Short installation guide
- Power supply
- Rubber feet

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	6	11.22	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	1.75

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

TP-Link Deutschland GmbH
Am Trippelsberg 100
Düsseldorf, Germany
<https://www.tp-link.com/de/>
support.de@tp-link.com