

MIKROTIK MikroTik RouterBOARD RB2011UiAS-RM

M-RB3011UIAS-RM
EAN 9010386000663



The RB3011 is a new multi port device, our first to be running an ARM architecture CPU for higher performance than ever before. The RB3011 has ten Gigabit ports divided in two switch groups, an SFP cage and for the first time a SuperSpeed full size USB 3.0 port, for adding storage or an external 3G/4G modem. RB3011UiAS-RM Unit comes with 1U rackmount enclosure, a touchscreen LCD panel, a serial console port and PoE output functionality on the last Ethernet port.

- CPU nominal frequency: 1.4 GHz
- CPU core count: 2
- Size of RAM: 1 GB
- 10/100/1000 Ethernet ports: 10
- Number of USB ports: 1
- Power Jack: 1
- PoE in: Yes

- Supported input voltage: 10 V - 30 V
- PoE out: Yes
- Voltage Monitor: Yes
- PCB temperature monitor: Yes
- Dimensions: 443x92x44mm
- Operating System: RouterOS
- Operating temperature range: -30 + 70 C
- License level: 5
- CPU: IPQ-8064-0-519FCBGA-TR-01-0
- Max Power consumption: 10W
- SFP ports: 1
- USB slot type USB 3.0: type A
- Serial port: RJ45
- Storage type: NAND
- Storage size: 128 MB

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.40	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.40	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.40	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	1.75

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

SIA Mikrotīkls

Ūnijas iela 2

Rīga, Latvia

<https://mikrotik.com>

support@mikrotik.com