## **MIKROTIK Routerboard BaseBox5**

## M-RB912UAG-5HPND-OUT EAN 9010386000717



The RB912 in an outdoor enclosure, fit with two RPSMA connectors for antennas, and a cable hood for protection against moisture. Also available are three additional places for antenna connectors, in case you wish to use the RB912 miniPCle slot for one more wireless interface to make a dual band device. The case can be opened with one hand, and is protected against the elements. USB, Ethernet and a Grounding wire exits are provided on the bottom, behind a protective door. Comes with a mounting loop for tower/pole mounting, and a separate DIN rail mount is also provided. Package also includes a PoE injector and power supply unit. Box contains: RB912 outdoor unit, PSU, PoE injector, mounting loop, DIN rail mount

- CPU nominal frequency: 600 MHz
- CPU core count: 1
- Size of RAM: 64 MB
- Architecture: MIPS-BE
- 10/100 Ethernet ports: 0
- 10/100/1000 Ethernet ports: 1
- MiniPCI slots: 0
- MiniPCI-e slots: 1



- Wireless chip model: AR9342-BL1A
- Wireless standards: 802.11a/n
- Number of USB ports: 1
- 802.3af support: No
- PoE: 8-30V DC
- Voltage Monitor: Yes
- PCB temperature monitor: Yes
- CPU temperature monitor: No
- Dimensions: 246x135x50mmOperating System: RouterOS
- Operating temperature range: -30C to +60C
- License level: L4
- Current Monitor: No
- CPU: AR9342-BL1A
- Max Power consumption: 14W at 24v
- SFP ports: 0
- SFP+ ports: 0
- USB slot type: USB type A
- Number of chains: 2

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.30	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.30	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.30	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	1.75

## More images:





## EU responsible person

 $\ensuremath{\mathsf{EU}}$  based economic operator ensuring the product complies with the required regulations.

SIA Mikrotīkls Ūnijas iela 2 Riga, Latvia https://mikrotik.com support@mikrotik.com