

DIGITUS® Fan unit for variable 483 mm (19") installation

DN-19 FAN-2-HO
EAN 4016032174240



Ventilation unit for 483 mm (19") installation 2 fans, thermostat, switch, grey (RAL 7035)

Also known colloquially as slide-in fans, the fan units can be mounted variably in the 19" grid of any network or server rack instead of under the roof. The scope of delivery includes mounting brackets for easy attachment in the 19" profile. Equipped with an ON/OFF switch and a shelf-mounted thermostat, each fan unit offers the best operational readiness according to individual requirements. The model is available in the standard colors grey (RAL 7035) and black (RAL 9005), optionally equipped with two or four fans.

The DIGITUS® 483 mm (19") accessories have been developed for the high demands of IT infrastructure and are manufactured to German quality standards.

- Variable installation in the 483 mm (19") level
- 2 fans
- incl. thermostat, adjustable from 0 °C to +70 °C
- On/off switch

- Noise level of fan unit with two built-in fans: 55-60 dB
- Noise level of a single fan in the fan unit: 50-55 dB
- Air flow rate: 4.6 m³/min.
- 1.8 m supply cable with CEE 7/7 (type F) plug
- Installation depth 4-point mounting (min. - max.): 170 - 220 mm

Attributes

- Color: light grey, RAL 7035
- Air flow: 4.6 m3/min
- Filter: no
- For cabinet series: all
- Inch form factor (IEC 60297): 482.6 mm (19")
- Mounting area: 482.6 mm (19")
- Quantity of mounted fans: 2

Package contents

- Mounting bracket set
- Power cable
- Fastening material

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	9	30.10	30.00	50.00	51.50	77,250.00
Packaging Unit Inside	1	3.34	23.50	51.50	6.00	7,261.50
Packaging Unit Single	1	3.34	23.50	51.50	6.00	7,261.50
Net single without Packaging	0	2.52	16.00	48.20	5.50	4,241.60

More images:

