

DIGITUS® CAT 6, modular couplers, shielded

AT-AG 8/8 C6S

EAN 4016032229032



Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0

- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

Attributes

- Category: CAT 6

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	9.80	54.00	35.00	12.00	22,680.00
Packaging Unit Inside	50	0.98	22.00	20.00	6.00	2,640.00
Packaging Unit Single	1	0.02	4.00	2.00	2.00	16.00
Net single without Packaging	0	33.00	0.00	0.00	0.00	0.00