

DIGITUS® Patch holder for wall mounting for 483 mm (19") installations

DN-19 PB-4U-SW
EAN 4016032250371



4U wall mounting patch bracket, 195x505x250 mm adjustable depth, stackable, black (RAL 9005)

The patch holders for wall mounting are used to install 483 mm (19") components. Depending on individual space requirements, they are available in various height units. The adjustable depth (from 250 mm up to 430 mm) enables the installation of larger components. A large punched-out area at the rear can be used for cable routing if the cables come directly out of the wall, for example.

- for the installation of 483 mm (19") components
- 1.1 - 1.5 thick sheet steel, powder-coated
- depth-adjustable (min. 250 mm; max. 430 mm)
- with four holes for wall mounting
- Back with cut-out for e.g. Cabling

Attributes

- Cabinet type: Wall mounting cabinet
- Color: black, RAL 9005
- Front door: without
- Load capacity: 15 kg
- Side panels: Both sides
- Units: 4
- Width: 505 mm
- IP protection class: without
- Mounted: no

Package contents

- Fastening material for stacking

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	5	18.20	23.50	55.50	22.00	28,693.50
Packaging Unit Inside	1	3.64	20.50	53.00	4.00	4,346.00
Packaging Unit Single	1	3.64	20.50	53.00	4.00	4,346.00
Net single without Packaging	0	0.00	25.00	50.50	19.50	24,618.80

More images:

