

DIGITUS® aluminum outlet strip, 10 outlets, 2 m supply IEC C14 plug

DN-95404

EAN 4016032266426



1U Aluminum PDU, rackmountable 10A, 2500W, 250VAC 50/60Hz, overI-prot.,1xC14

The DIGITUS® power distribution unit is the perfect solution for your network or server cabinet. In terms of power distribution, the PDU meets requirements of many applications in IT, network technology and laboratories. With its IEC60320 C13 input connector, the PDU can be ideally used as an additional 19" distribution for a UPS. The individual C13 outputs are equipped with a pull-out protection.

Safe and professional power in the 482.6 mm (19") range

- Pull-out protection on each output (for C13 standard cable)
- 10A input fuse protects against overload
- Horizontal 19" installation in the rack
- Housing: Aluminum profile
- Plastic components made of ABS UL-94V-0
- Input: IEC60320 C14 plug, 230 Vac / 10 A
- Output: appliance sockets 10 x IEC60320 C13, max. 10 A per output, integrated pull-out protection for each output

- Supply cable: cable cross-section: 1.5 mm² , length: 2 m
- Dimensions: 482.6 (19") x 45 x 45 mm (HxWxD)
- Approvals: CE mark

Attributes

- Current: 10 A
- Input Plug: IEC 60320 C14 inlet
- Installation: Rack 1U
- Outlets: IEC 60320 C13
- Phase: 1ph
- Power: 2,3 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Package contents

- Scope of delivery: 1 socket strip, 2 mounting brackets; 1 safety instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	21.00	104.00	46.00	27.00	129,168.00
Packaging Unit Inside	1	1.05	6.80	50.00	9.10	3,094.00
Packaging Unit Single	1	1.05	6.80	50.00	9.10	3,094.00
Net single without Packaging	0	0.73	4.40	48.20	4.50	954.36

More images:

