

# DIGITUS® DisplayPort Connection Cable, 3m

AK-340100-030-S  
EAN 4016032288961



### DisplayPort Connection Cable, Type DP M/M, 3.0m, w/interlock, UHD 4K, DP 1.2, bi

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

#### Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Support up to 4K/2K with 60Hz
- Supported Video format: 4K (3840x2160) @ 60 Hz, Full HD (1920x1080) @ 120 Hz
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)
- HDCP-Version: HDCP 1.3

#### Attributes

- Assortment: DisplayPort Cables

- AWG: 30
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CCS
- Length: 3 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	50	8.30	22.00	31.00	55.00	37,510.00
Packaging Unit Inside	10	1.66	7.00	31.00	35.00	7,595.00
Packaging Unit Single	1	166.00	16.00	15.00	3.50	840.00
Net single without Packaging	0	0.12	13.50	13.00	3.00	526.50

More images:

