

# DIGITUS® mini GBIC (SFP) Module, 1.25 Gbps, 0.55km

DN-81000

EAN 4016032305651



## 1.25 Gbps SFP Module, Multimode LC Duplex Connector, 850nm, Up to 550m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

### The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable

- Connector: 1x LC Duplex
- 1000Base-SX - For Short Haul
- Wavelength: 850nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- For a Distance of up to 0.55km
- Suitable for 50/125µm and 62.5/125µm multimode fiber cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C

### Attributes

- Mode: Multimode
- Connector: LC
- Distance (km): 0.5
- Wavelength: 850 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Gigabit

### Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	3.10	11.80	9.30	340,194.00
Net single without Packaging	0	0.02	1.00	5.90	0.80	4.72

More images:

SFP Modules	SKU Code	Speed	Distance	Connector	Wavelength	Operating Temperature	Additional Features
Fast Ethernet	DS-4101	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
	DS-4102	10/100/1000	10km	LC	1550nm	-40 to 70 °C	
	DS-4103	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
SFP+	DS-4104	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
	DS-4105	10/100/1000	10km	LC	1550nm	-40 to 70 °C	
	DS-4106	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
10G	DS-4107	10G	10km	LC	1310nm	-40 to 70 °C	
	DS-4108	10G	10km	LC	1550nm	-40 to 70 °C	
	DS-4109	10G	10km	LC	1310nm	-40 to 70 °C	
Fast Ethernet	DS-4110	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
	DS-4111	10/100/1000	10km	LC	1550nm	-40 to 70 °C	
	DS-4112	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
SFP+	DS-4113	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
	DS-4114	10/100/1000	10km	LC	1550nm	-40 to 70 °C	
	DS-4115	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
SFP+	DS-4116	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
	DS-4117	10/100/1000	10km	LC	1550nm	-40 to 70 °C	
	DS-4118	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
SFP+	DS-4119	10/100/1000	10km	LC	1310nm	-40 to 70 °C	
	DS-4120	10/100/1000	10km	LC	1550nm	-40 to 70 °C	
	DS-4121	10/100/1000	10km	LC	1310nm	-40 to 70 °C	

