

DIGITUS® DisplayPort adapter cable

AK-340306-020-S
EAN 4016032328537



DisplayPort Adapter Cable, Type DP-DVI (24+1) M/M, 2.0m, w/interlock, DP 1.1a comp., bl

This digital HD cable converts DisplayPort signals into DVI signals and is ideal for connecting devices with a DisplayPort interface to an HD-compatible TV, projector or monitor with a DVI interface.

Connect a DVI-capable monitor to a DisplayPort video card/source

- Supports up to 1080p with 60 Hz
- Copper cores, foil and braid shielded for robustness and a reliable connection
- Plug and play, no additional driver required
- Supported transmission modes: RBR, HBR, HBR2
- Maximum bandwidth: 10.8 Gbps
- HBR version/transfer mode: HBR1 (2.70 Gbit/s per lane)
- HDCP version: HDCP 1.3
- OFC solid copper cable (99.9 % oxygen-free)

Attributes

- Assortment: DisplayPort Cables
- AWG: 30
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DVI-D, (24+1), plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Resolution max.: 1920 x 1080 Pixel, 60Hz
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	6.50	28.00	34.00	45.00	42,840.00
Packaging Unit Inside	5	0.65	22.00	15.00	2.00	660.00
Packaging Unit Single	1	0.13	22.00	15.00	2.00	660.00
Net single without Packaging	0	0.13	22.00	15.00	2.00	660.00

More images:

