

# DIGITUS® Network cabinet Unique series - 800x800 mm (WxD)

DN-19 36U-8/8-1

EAN 4016032332329



## 36U network rack, Unique 1787x800x800 mm, color grey (RAL 7035)

The network cabinets in the Unique series have been designed and produced for particularly convenient and flexible network cabling. Sophisticated optimizations offer market-compliant stability with maximum flexibility. A modular base chassis, which can be opened using screwed 483 mm (19") blind panels, offers sufficient space for cables of all kinds. In addition, there are side cable inlets with brushes at the top and bottom of the enclosure, as well as another at the rear of the base chassis. Rear brush strips above and below the rear door (from 26U) enable use in a wide range of application scenarios. Generous vertical cable ducts with cable routing aids and cover, installed in the front (from 800 mm enclosure width), perfectly round off the versatile features of the network enclosure. Two pairs of cranked and galvanized 483 mm (19") profile rails, labelled with height units that can be read in opposite directions, are installed inside. They are infinitely adjustable and are connected to additional depth struts in the cabinet. Each enclosure is a robust steel construction made from sheet steel up to 1.5 mm thick. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). Modular lockable and removable side panels and doors improve accessibility. Door hinges can be changed. Furthermore, the cabinets can be completely dismantled if required thanks to the demountable design. Depending on the application, all DIGITUS® Unique network cabinets can also be used as server cabinets, taking into account factors such as the weights and heat development of built-in components. The installation of perforated sheet steel doors in such variants ensures improved passive cooling of the installed components. For example, a model defined by DIGITUS® as a server cabinet is supplemented by rear PDU brackets in the standard configuration of the Unique Server-N series.

**The DIGITUS® network cabinets of the Unique series combine maximum stability with optimum flexibility in cable management, for the high demands of modern IT infrastructure with a wide variety of application scenarios.**

- Protection class IP20
- Protection class (IK impact resistance level): IK07
- Front door made of complete steel frame with certified safety glass, one-piece
- Swivel handle with profile half-cylinder lock incl. type 333 key on the front door
- Steel rear door with round lock incl. key type 333, two-part

- 1-point locking on the front door, 1-point locking on the rear door (incl. locking aid at the top and bottom)
- Removable side panels with type 333 sash lock and additional snap lock
- Incl. 4 M10 leveling feet, enclosed
- 483 mm (19") profile rails mounted at the front and rear inside the enclosure, infinitely adjustable
- 483 mm (19") profile rails are galvanized and numbered in opposite directions to the height units
- 483 mm (19") profile rails are connected to depth struts for increased stability
- High load capacity of the 483 mm (19") profile rails of up to 1200 kg
- Installation depth for components min. - max.: 563 - 743 mm
- Vertical cable ducts with cable routing aids and cover installed in the front panel
- Modular, openable base chassis with removable 19" blind panels (450 x 537 mm)
- Cable inlets in the base: 400 x 170 mm (rear), 90 x 550 mm (side)
- Cable inlets in the roof: 90 x 550 mm (lateral)
- Roof is prepared to accommodate a fan unit and an attached, removable cover
- Earthing points in the cabinet and on removable doors/walls
- Ready for immediate use: Delivery is assembled (cabinet can be completely dismantled if required)

### Attributes

- Cabinet type: Network cabinet
- Color: light grey, RAL 7035
- Depth: 800 mm
- Front door: Glass door, single opening
- Load capacity: 1200 kg
- Rear door: Steel door, closed, double opening
- Side panels: Both sides
- Units: 36
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes

### Package contents

- Earthing cable set
- Installation set (screws, cage nuts, washers)
- 2 x key
- 4 x leveling foot, M10

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	97.00	85.00	85.00	183.70	1,327,230.00
Packaging Unit Inside	1	97.00	85.00	85.00	183.70	1,327,230.00
Packaging Unit Single	1	97.00	85.00	85.00	183.70	1,327,230.00
Net single without Packaging	0	96.00	80.00	80.00	178.70	1,143,680.00

More images:

