

DIGITUS® Active DisplayPort to HDMI Converter

AK-340415-002-S
EAN 4016032427476



DisplayPort Adapter Cable, Type DP - HDMI A M/F, 0.2m, w/lock, HDMI 2.0, act., gold, bl

The 4K DisplayPort to HDMI Converter (DisplayPort male to HDMI female) enables to reflect your contents from your computer or notebooks to your TV. It supports a resolution up to 4096 x 2160. So you can show your pictures, videos, documents, presentations, etc. in Ultra HD and use it optimal in meetings or in private areas.

HDMI 2.0 feature support

- Integrates a complete DisplayPort receiver and complete HDMI transmitter for video format conversation
- Integrated HDMI2.0 transmitter, up to supporting 4K x 2K@60Hz, 4K x 2K@30HZ and 1080P / 3D videos.
- Support DP++ Dual-Mode
- Supports DisplayPort 1.2 and 4 lanes at 1.62Gbps, 2.7Gbps and 5.4Gbps
- Full HDCP 1.4 / 2.2 content protection support.
- Deep Color 24bit
- Audio input formats: 8-ch LPCM, compressed audio (AC-3, DTS) and HBR audio format up to 24-bit audio sample size and 192 khz frame rate.

- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)

Attributes

- AWG: 32
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: HDMI type A, jack
- Connector 2: HDMI type A, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Wire material: CU
- Length: 0.2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	8.00	38.10	30.20	24.10	27,729,900.00
Packaging Unit Inside	10	0.40	33.00	27.90	7.60	6,997.32
Packaging Unit Single	1	0.04	20.00	15.00	1.52	456.00
Net single without Packaging	0	32.00	25.20	3.50	1.40	123.48

More images:

