

DIGITUS 2 Port Universal Outdoor Fast Ethernet PoE+ Extender, 803.2af/at, 75 W

DN-95126

EAN 4016032455769



Outdoor 1 to 2 UPoE Extender IEEE803.2af/at 1 port in 95W, 2 ports out supports 75W/30W/15,4W

The DIGITUS® outdoor universal PoE+ extender is a PoE extender in a weatherproof housing with the IP67 protection class. The housing is very sturdy and conforms to the IK10 vandalism protection class. The UPoE+ extender offers the extension of the network signal by another 100m between the switch and PoE terminal devices such as IP surveillance cameras or access points without additional power supply. The extender requires no settings to be made thanks to plug and play.

Extend your PoE Ethernet signal without additional power supply by up to 200 m

- Meets the 802.3af/at PoE standard & UPoE 95 W input / 75 W output
- 1 port 10/100BaseTX PoE IN
- 2 port 10/100BaseTX PoE OUT
- Network capacity: 10/100 Mbps Fast Ethernet

- Output voltage per PoE port: 44 – 55V/DC, max. 75W
- PoE overvoltage protection up to 6kV
- No additional power supply unit required
- Power supply (input) via pin: 4/5 (+), 7/8 (-) and 3/6 (-), 1/2 (+)
- Power supply (output) via pin: 4/5 (+), 7/8 (-) and 3/6 (-), 1/2 (+)
- Protection level: IP67
- Vandalism protection class: IK10
- Dimensions: 167.5 x 72.8 x 39.8 mm
- Weight: 0.36kg
- Storage temperature: -40°C – 85°C
- Operating humidity: 10 – 90% non-condensing

Attributes

- Industrial usage: no

Package contents

- Outdoor 2 port UPoE+ extender, IEEE802.3af/at
- Quick start guide

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	30	14.50	19.50	44.00	51.00	43,758.00
Packaging Unit Inside	1	0.48	6.00	9.00	20.00	1,080.00
Packaging Unit Single	1	0.48	6.00	9.00	20.00	1,080.00
Net single without Packaging	0	0.36	3.90	7.20	16.70	468,936.00

More images:

