

DIGITUS USB 3.0 Gigabit SFP Network Adapter

DN-3026

EAN 4016032457138



USB3.0 Gigabit SFP Network Adapter additional SFP module needed

The USB 3.0 Gigabit SFP adapter allows you to extend your laptop to an SFP connection and to connect directly to a fiber optic network via a suitable fiber optic transceiver. This fiber optic interface is the right choice both for mobile use in connection with laptops and for stationary use in desktop systems. In addition, this SFP adapter in data and server centers serves its purpose in monitoring and troubleshooting applications, allowing you to intervene into the fiber optic infrastructure directly and with full bandwidth. It is easy to use, offers a wealth of options and is the perfect complement for most computers that do not have an SFP connection as a standard feature. Thanks to the virtual drive, no driver installation from CD is necessary - plug in and get started. The power supply is also ensured via the USB 3.0 interface. If Wi-Fi connections pose a security risk and copper connections are too slow, fiber optic connectivity provides the right solution for your network. The adapter is compatible with Windows, macOS, Google Chrome and all other systems that are compatible with USB 3.0.

Extend your laptop with USB 3.0 port to a complete Gigabit SFP network connection.

- Supports USB 3.0 ports
- Fast Gigabit data transfer
- Chipset: RTL8153/Realtek
- Advanced energy-saving options via USB 3.0
- Supports IEEE802.3az-2010 (EEE)
- Network standards: IEEE 802.1p IEEE 802.1Q IEEE 802.2 IEEE 802.3ac IEEE 802.3az IEEE 802.3x, IEEE 802.3z IEEE 802.3ad

- Additional Features: IPMI pass-through via SMBus or NC-SI, WoL, PXE remote boot, iSCSI boot, VLAN filtering
- Compatible with Microsoft NDIS5, NDIS6 (IPv4, IPv6, TCP, UDP) checksum features
- Supports IEEE802 IP Layer 2 priority encoding and IEEE802.1Q VLAN (Virtual bridged Local Area network)
- Supports 1000Mbps-SX/LX transceiver
- Supports USB 3.0, USB 2.0 and USB 1.1
- Supports CDC-EMC (Device Class & Ethernet Control Model)
- Supports LPM (Link Power Management)
- Supports Pair swap / polarity / skew correction
- Crossover Detection & Auto-Correction
- Integrated transmit/receive buffer support
- Supports hardware CRC (Cyclic Redundancy Check) function
- Supports power down / link down, power saving
- Upstream port: USB 3.0 AF
- Downstream port: SFP Port
- Operation temperature: 0 – 70°C
- Operating humidity: 10 – 90% (non-condensing)
- Operating humidity: 10 – 90% (non-condensing)
- Power Consumption: 2.5 W
- Power consumption on standby: 0.7 W
- Cable length: 17 cm
- Measurements: L 7.1 x B 4.5 x T 1.8 cm
- Weight: 50 g

Package contents

- 1 x USB 3.0 Gigabit SFP Network Adapter
- 1 x Manual
- 1 x CD-ROM
- SFP module not included in package content.

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	90	11.00	41.00	41.00	39.00	65,559.00
Packaging Unit Inside	1	0.12	12.60	17.50	3.20	705.60
Packaging Unit Single	1	0.12	12.60	17.50	3.20	705.60
Net single without Packaging	0	0.05	4.50	29.00	1.80	234.90

More images:

