

# CAT 6A U/FTP Slim patch cord

DK-1624-A-025S  
EAN 4016032469186



## CAT 6A U-FTP slim patch cord, Cu, LSZH AWG 28/7, length 2,5 m, color grey

DIGITUS® slim patch cords are characterised by their small outer diameter and flexible sheath. Slim design enables versatile use in your network. Moreover, the DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

**Enables flexible and space-saving cabling in your network**

- 2x RJ45 connectors (8P8C)
- Covers with kink protection, strain relief and latch protection
- Length indication on hoods
- Inner conductors: Copper (Cu)
- Anti-kink sleeve: molded-on
- Connector 1 type: RJ45 8(8)
- Connector 2 type: RJ45 8(8)
- Flame retardant version: yes
- Latch protection: yes
- NVP value: 76
- Oil resistant to EN 60811-404: no
- Bending radius: 4D (outer diameter x 4)
- Configuration: 1:1
- Category: CAT 6A
- Shielding: U-FTP, pairs in metal foil
- Length: 2.5 m
- Color: grey
- Jacket: LSOH
- Slim Version: yes
- Structure: 4 x 2 AWG 28/7, twisted pair

## More images:



