

# DIGITUS® Wireless HDMI KVM Extender Set, 200 m

DS-55321

EAN 4016032478812



### Wireless HDMI KVM Extender Set 200 m, Full HD

The Wireless HDMI® KVM Extender Set transmits your HDMI® video and audio signals in Full HD resolution wirelessly over a distance of up to 200 m (unrestricted view). Thanks to KVM functionality, a mouse/keyboard can be connected to the receiver unit, allowing the signal source to be controlled directly at the output device. A local monitor can be connected via the HDMI loop-out on the transmitter unit to control the output on the receiver. The auto-pairing function promises simple installation.

### Transmits HDMI video and audio signals wirelessly in Full HD over a distance of up to 200 m in clear view and offers KVM functionality

- Wireless HDMI signal transmission up to 200 m (unobstructed view)
- Supports transmission resolutions up to 1920x1080p
- Radio channel: IEEE 802.11ac, 5 GHz, 2T2R
- Authentication protocol: WPA2 (WPAS-PSK / WPA2-Enterprise)
- Transmitter unit connections:
  - 1x HDMI input (signal source, 4K/60Hz)
  - 1x HDMI loop-out / output
  - 1x Micro USB input (power supply, DC 5V/1A)
  - 1x IR output - connection of IR transmitter to control the signal source
  - 1x Micro USB input - data connection of the source for using the KVM function
- Receiver unit connections:
  - 1x HDMI output (output device, 1080p/60Hz)
  - 1x USB-A input (connection of mouse/keyboard)
  - 1x Micro USB input (power supply, DC 5V/1A)

- 1x reset button
- Power consumption: 2.5W
- Operating temperature: 0-40°C
- Compression: H.264
- Dimensions (1 unit): L 7.9 x W 15.5 x H 2.2 cm
- Weight (1 unit): 326 g
- Color: black
- The transmission distance with limited visibility cannot be determined across the board and depends on the conditions on site
- Walls, glass, etc. shorten the signal coverage or cause signal loss

### Attributes

- HDTV Standard: Full HD
- Resolution max.: 1920 x 1080 Pixel, 60Hz
- Distance: 200 m
- KVM: yes
- PoE (Power over Ethernet): no
- Video connection ports: HDMI

### Package contents

- 1x transmitter unit
- 1x receiver unit
- 2x power supply unit (DC 5V/1A, 0.75 m)
- 1x IR transmitter (1.5 m)
- 3x Micro USB - USB-A cable (0.5 m)
- 1x operating instructions
- 2x HDMI cable (1.5m)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	11.60	26.00	34.00	47.00	41,548.00
Packaging Unit Inside	1	1.16	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.16	25.00	23.00	6.60	3,795.00
Net single without Packaging	0	326.00	7.90	15.50	2.20	269.39

More images:

