

DIGITUS® HDMI® Splitter, 1x2, 4K / 30 Hz

DS-45340

EAN 4016032483656



4K HDMI Splitter, 1x2 4K/30Hz, black

Splits an HDMI input signal onto two output displays. It supports a maximum resolution of 4K2K/30Hz. Via an EDID changeover switch, two modes can be selected (Copy: HDMI output 1 / Auto mode: Automatically compares HDMI output 1&2 and merges together a new EDID and plays this back to the HDMI input

Splits an HDMI input signal onto two output displays with a maximum resolution of 4K2K/30Hz

- Splits an HDMI input signal onto two output displays with a maximum resolution of 4K2K/30Hz
- EDID support (2 modes) - 1: Copy - HDMI output 1 / 2: Auto Mode - Compare & create HDMI output 1 & 2
- HDMI 1.4b
- HDCP 1.4
- Video bandwidth: 2.97 Gbps
- Compact design for easy and flexible installation
- Connections:
- 1x HDMI input (4K/30Hz) - Connection signal source
- 2x HDMI output (4K/30Hz) - Connection output device

- 1x Power adapter input (DC 5V/1A), connection for external power adapter
- 1x EDID changeover switch
- Operating temperature: 0-40°
- ESD protection
- Housing: Metal
- Dimensions: L 7 x W 6 x H 2 cm
- Weight: 125 g
- Color: black

Attributes

- HDTV Standard: Ultra HD 4K
- Number of ports: 2
- Resolution max.: 3840 x 2160 Pixel, 30Hz
- Signal output: HDMI
- Video connection ports: HDMI

Package contents

- 1x HDMI splitter
- 1x Power adapter (DC 5V/1A, 1.15 m)
- 1x User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	11.00	25.30	35.00	44.50	39,404.80
Packaging Unit Inside	1	275.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	275.00	10.50	117.00	6.50	7,985.25
Net single without Packaging	0	125.00	7.00	6.00	2.00	84.00

More images:

