

# DIGITUS® Basic IT PDU, 3-phase 16A, 24 x C13, 3 x C19, 3 m supply cable, IEC 60309 16 A plug

DN-95452

EAN 4016032485971



## IT BASIC PDU, 3PH, 16A, 24 x C13, 3 x C19 Vertical, 3m cable, IEC309 3Ph-16A plug

The DIGITUS® power strips are the perfect solution for your network or server cabinet. In terms of power distribution, the PDU meets the requirements of many applications in IT, network technology and laboratories. The individual C13 and C19 outlets are equipped with pull-out protection. It is designed for vertical installation, which saves height units and provides more space for additional devices. The socket strip with 27 outlets has excellent physical properties and is designed for an output of up to 4,000 W (250VAC / 16A), enabling the best performance to be achieved with the corresponding load.

### Secure and professional power distribution solution for demanding IT requirements in network and server cabinets

- Pull-out protection on each output (for C13 and C19 standard cables)
- Vertical installation
- Housing: Aluminum profile
- Plastic components made of ABS UL-94V-0
- Mains cable: IEC60309 3ph/N/PE 6h, 230V / 16A plug

- Supply line: 3 m
- Max. Load: 4000 W / 250 V AC / 16 A (50/60Hz)
- Sockets: 24 x C13 socket outlet, 3 x C19 socket outlet
- Output current: C13 (10A), C19 (16A)
- Rated voltage: 230–250 VAC, 50/60 Hz
- Dimensions (L x W x D): 1288.5 x 45 x 60 mm
- Color: Black

### Attributes

- Current: 16 A
- Input Plug: IEC 60309 16A 3ph/N/PE 6h
- Installation: Rack OU
- Outlets: IEC 60320 C13, IEC 60320 C19
- Phase: 3ph
- Power: 11 kVA
- Volts: 230 / 400 V

### Package contents

- Scope of delivery: 1 socket strip, 1 safety instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

