

DIGITUS KVM Switch, 2x1 DP, DP Out,USB

DS-12851
EAN 4016032487869



KVM Switch, 2x1 DP, DP Out,USB 2 x DP + 2x USB +2 Speaker + 2 Micro

The DS-12851 is an advanced desktop KVM switch that offers seamless switching between two groups of DP+ audio +MIC+USB devices. It comes equipped with a set of local control interfaces that allow you to easily manage and control all of your connected devices. The front USB interface provides easy access for connecting USB peripherals such as a keyboard, mouse, USB flash drive, printer, and more. With support for both hotkey switching and panel button switching control, the DS-12851 makes it easy to switch between your devices on the fly, without any interruption to your workflow. Whether you're a professional working on multiple projects or a gamer looking for seamless control over your gaming setup, the DS-12851 has got you covered. With its sleek and compact design, the DS-12851 is perfect for use in a wide range of settings, including home offices, gaming rooms, and professional workspaces. So if you're looking for a reliable and easy-to-use interface controller that can keep up with your demanding needs, look no further than the DS-12851.

With a resolution of 4K @ 60HZ and two DisplayPort inputs, this KVM switch offers impressive image quality and flexibility when connecting to multiple devices. The additional connections on the front panel and support for Dolby True HD and DTS HD Master Audio make it a versatile choice for all kinds of applications.

- Resolution: 4K @ 60HZ(3840x2160 @60HZ)
- Inputs: 2 x Displayport inputs (2x1), 2 x USB B, 2 x audio combo jack 3.5 mm jack (microphone, speaker)
- Outputs (console): 1 x display port, 2 x USB A (mouse, keyboard), 2 x stereo audio 3.5m jack (microphone, loudspeaker)
- Additional connection on the front: 1 x USB A for further peripheral devices, such as printers or USB sticks
- USB specification: USB 2.0 compliant (FullSpeed)
- Supported audio formats: Dolby True HD, DTS HD Master Audio
- Switching between PCs: Switch on front panel or hot keys
- Status LED on front panel shows current configuration
- The unit works platform-independently, suitable for all operating systems
- Operating temperature: 0°C ~ 50°C
- Storage temperature: -20°C ~ 60°C
- Operating humidity: 0 - 80% RH (non-condensing)
- Housing material: metal
- Power supply: via USB or optional 9 V DC power supply unit
- Dimensions: 13.2 x 9.2 x 4.4 cm (WxDxH)
- Weight: 465 g

Package contents

- 1 pc Host KVM switch
- 2 sets of custom KVM connection cables
- 1 user manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	1.00	38.50	24.00	49.00	45,276.00
Packaging Unit Inside	1	0.10	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.10	9.30	18.50	22.50	3,871,120.00
Net single without Packaging	0	0.46	6.60	9.20	13.20	801,504.00

More images:

