

# DIGITUS® SOHO Pro wall-mounted enclosure - 254 mm (10") - 315x300 mm (WxD)

DN-49105

EAN 4016032493679



**10" 12U wall mounting cabinet, SOHO Pro 595 x 315 x 300 mm, unmounted, black**

Whether in the home, office or in sub-distribution boards with limited space: With the compact 254 mm (10") solutions from the SOHO Pro series, you can install your network wherever you want. Available in three height units (6U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry in the roof and base. A pair of galvanized 254 mm (10") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

**The DIGITUS® wall-mounted enclosure SOHO Pro series is characterized by efficient delivery in an optimized flat pack and particularly user-friendly installation.**

- Protection class IP20
- Lockable safety glass door, type 9473
- 200° door opening angle
- 1-point locking on the front door
- 254 mm (10") profile rails mounted at the front inside the enclosure, galvanized

- 254 mm (10") profile rails are adjustable in depth
- 1.1 - 1.5 thick sheet steel with a high load-bearing capacity, powder-coated
- Cable entry with brush strip in the roof and with plastic cover in the floor
- Ventilation slots for active and passive ventilation
- Installation depth for components max.: 254 mm
- Product dimensions (H x W x D): 595 x 315 x 300 mm
- Packaging dimensions (H x W x D): 175 x 360 x 610 mm
- Weight (net / gross): 7.92 / 8.39 kg

**Attributes**

- Cabinet type: Wall mounting cabinet
- Color: black, RAL 9005
- Depth: 300 mm
- Front door: Glass door, single opening
- Load capacity: 30 kg
- Side panels: Both sides
- Units: 12
- Width: 316 mm
- IP protection class: IP20
- Mounted: no

**Package contents**

- 2x key
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	8.39	61.00	36.00	17.50	38,430.00
Packaging Unit Inside	1	8.39	61.00	36.00	17.50	38,430.00
Packaging Unit Single	1	8.39	61.00	36.00	17.50	38,430.00
Net single without Packaging	0	7.92	30.00	31.50	59.50	0.00

More images:



**DN-49105**  
Wall Mounting Cabinet 5040 PRO  
254mm (10") - 315x200mm (WxD)

**DIGITUS**

- Slide the bottom panel into the slots in the direction of the arrows. If you encounter the resistance of the bottom panel, lift the cabinet by the top handle to the ground to clear the bottom panel. Insert the bottom panel into the bottom gap of the body. Assemble the bottom panel in the body by a screw.
- Put the cabinet on the floor, the bottom panel facing the ground. Bend the mounting of the bottom panel downwards and the hinges of the top panel upwards.
- Show the QR code your camera to watch the installation video. Scan the QR code to watch the video.

**DN-49105**  
Wall Mounting Cabinet 5040 PRO  
254mm (10") - 315x200mm (WxD)

**DIGITUS**

- Insert the top panel into the top of the body. Lay down the top panel of the body so that the top edge of the body is at the bottom. Open the finger side panels of the body.
- Slide the top panel into the body in the direction of the arrows. As soon as the cabinet is inserted, insert the hinges of the panel into the gap of the body. Fit the top panel to the body by the screws. Finger side supports have already been mounted to be on the back side of the glass door.
- Insert the top hinge pin of the glass door into the finger lock of the top panel.