

DIGITUS® Wall-mounted enclosure SOHO Pro - 483 mm (19") - 540x400 mm (WxD)

DN-49204

EAN 4016032493730



19" 9U wall mounting cabinet, SOHO Pro 460 x 540 x 400 mm, unmounted, grey

Whether in the home, office or for sub-distribution boards with limited space: With the compact 483 mm (19") solutions from the SOHO Pro series, you can install your network wherever you want. Available in four height units (4U, 7U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry in the top and bottom. Two pairs of galvanized 483 mm (19") profile rails, labelled with legible height units, are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

The DIGITUS® wall-mounted enclosure SOHO Pro series is characterized by efficient delivery in an optimized flat pack and particularly user-friendly installation.

- Protection class IP20
- Lockable safety glass door, type 9473
- 200° door opening angle
- 1-point locking on the front door

- 483 mm (19") profile rails mounted at the front and rear inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth
- 1.1 - 1.5 thick sheet steel with a high load-bearing capacity, powder-coated
- Cable entry with plastic cover in the roof and floor
- Ventilation slots for active and passive ventilation
- Installation depth for components max.: 319.25 mm
- Product dimensions (H x W x D): 460 x 540 x 400 mm

Attributes

- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 400 mm
- Front door: Glass door, single opening
- Load capacity: 60 kg
- Side panels: Both sides
- Units: 9
- Width: 540 mm
- IP protection class: IP20
- Mounted: no

Package contents

- 2x key
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	11.44	58.00	47.50	17.50	48,212.50
Packaging Unit Inside	1	11.44	58.00	47.50	17.50	48,212.50
Packaging Unit Single	1	11.44	58.00	47.50	17.50	48,212.50
Net single without Packaging	0	10.58	40.00	54.00	46.00	0.00

More images:



DN-45204
Wall Mounting Cabinet S010 PRO
483mm (19") - 540x400mm (WxD)

DIGITUS

- Use the 19" slide cabinet out of the box.
- Slide the bottom plate into the body to the installation of the cabinet. As soon as the cabinet is in the position of the bottom plate the top edge of the body.
- Slide the cabinet into the body by the bottom. Push the cabinet into the body until the top edge of the cabinet is flush with the top edge of the body. Push the cabinet into the body until the top edge of the cabinet is flush with the top edge of the body. Push the cabinet into the body until the top edge of the cabinet is flush with the top edge of the body.
- Lock the body down and bottom panel to the wall.

DN-45204
Wall Mounting Cabinet S010 PRO
483mm (19") - 540x400mm (WxD)

DIGITUS

- Slide the cabinet into the body by the bottom. Push the cabinet into the body until the top edge of the cabinet is flush with the top edge of the body. Push the cabinet into the body until the top edge of the cabinet is flush with the top edge of the body.
- Lock the body down and bottom panel to the wall.