

DIGITUS® FTTH housing, 2 x LC/APC DX coupler with shutter

DN-931097

EAN 4016032498599



FTTH Outlet, with 2x LC (APC) DX adapter Surfacement

The fiber optic connection box is designed as an optical telecommunications housing. It is an ultra-compact housing for managing up to 4 fibers in the home, which can be easily wall-mounted and provides the connection point for up to 4 end devices. It is pre-assembled with 2 x LC/APC duplex couplers and offers flexible cable entries. It efficiently combines the possibility of fiber splices, terminations, storage and connections in the smallest possible space. The screw holes on the rear also allow for easy installation and positioning, with the housing flush with the wall.

FTTH housing in a minimalist design for the distribution of up to 4 fibers. The compact protective housing is perfect for FITH and office cabling for fiber optic splices, terminations and connections.

- Design : Suitable for wall and DIN rail mounting
- Wall mounting: Surface mounting

- Transmission technology : Fiber optics
- Integrated splice cassette
- Fiber type : Singlemode
- Connector interface: LC Duplex
- Connector type : LC/APC with shutter
- Number of ports: 4
- Number of equipped ports: 2
- Housing material: PC + ABS
- Protection class: IP45
- Operating temperature: -40°C ~ +85°C
- Color: White
- Dimensions: (LxWxH): 80 x 80 x 30 mm
- Weight: 0.07 kg

Package contents

- FTTH housing, 2 x LC/APC DX coupler with shutter

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	225	14.60	45.00	45.00	25.00	50,625.00
Packaging Unit Inside	1	0.06	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.06	8.60	8.00	2.80	192.64
Net single without Packaging	0	61.00	8.60	8.00	2.80	0.00

More images:

