

# DIGITUS Wall-mounted enclosure SOHO Pro - 483 mm (19") - 540x400 mm (WxD)

DN-49209

EAN 4016032499039



## 19" 9U wall mounting cabinet, SOHO Pro perforated door, 460 x 540 x 400 mm, unmounted, gr

Whether in the home, office or for sub-distribution boards with limited space: With the compact 483 mm (19") solutions from the SOHO Pro series, you can install your network wherever you want. The variant with a front door made of perforated sheet steel is available in three height units (7U, 9U, 12U). All cabinets are equipped with a cable entry in the top and bottom. Two pairs of galvanized 483 mm (19") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

**The DIGITUS® wall-mounted enclosure SOHO Pro series is characterized by efficient delivery in an optimized flat pack and particularly user-friendly installation.**

- Protection class IP20
- Lockable steel front door with perforation
- 200° door opening angle
- 1-point locking on the front door

- 483 mm (19") profile rails mounted at the front and rear inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth
- 1.1 - 1.5 thick sheet steel with a high load-bearing capacity, powder-coated
- Cable entry with plastic cover in the roof and floor
- Ventilation slots for active and passive ventilation
- Installation depth for components max.: 327 mm
- Product dimensions (H x W x D): 460 x 540 x 400 mm

### Attributes

- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 400 mm
- Front door: Steel door, perforated, single opening
- Load capacity: 60 kg
- Side panels: Both sides
- Units: 9
- Width: 540 mm
- IP protection class: IP20
- Mounted: no

### Package contents

- 2x key
- 1x QIG

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 1            | 15.30       | 46.00      | 59.00      | 19.00       | 51,566.00 |
| Packaging Unit Inside        | 1            | 15.30       | 46.00      | 59.00      | 19.00       | 51,566.00 |
| Packaging Unit Single        | 1            | 15.30       | 46.00      | 59.00      | 19.00       | 51,566.00 |
| Net single without Packaging | 0            | 14.00       | 40.00      | 54.00      | 46.00       | 0.00      |

**More images:**

