

# DIGITUS® Fiber optic splice cassette for 12 fibers incl. splice holder for crimp and shrink splice protection

DN-96106

EAN 4016032501329



### FO Splice Cassette, Crimp and Shrinkable tubings Upto 12 cores, incl. cover and splice holder

The fiber optic splice cassette is a versatile solution for the structured and efficient storage of up to 12 splice connections. It is supplied with holders for crimp and shrink splice protection, offering flexibility for different installation requirements. The design enables clear and secure fiber routing and ensures compliance with bend radius specifications to ensure long-term performance and reliability of splices. The secure fixation of the splices reduces the risk of micro-bending losses and minimizes mechanical stress on the fibres - especially in environments with vibrations or temperature fluctuations. Optimized for seamless integration into standard 19" patch panels and fiber optic distribution enclosures, the cassette ensures a clean, professional storage of each fiber termination point. Thanks to its compact format, the cassette enables high-quality fiber management that maintains clarity and accessibility for technicians during maintenance or future expansions. With a focus on durability, user-friendly handling and universal compatibility, the splice cassette is an indispensable element for structured cabling in networks, enterprise infrastructures and FTTH applications.

### Compact splice cassette for structured splice storage of up to 12 fibers. Supports both crimp and shrink splice protection with integrated holders. Reliably protects the spliced fibers in patch panels or housings.

- Fiber capacity: Up to 12 fibers
- Supported splice types: Crimp splices and Heat shrink splice protection
- Splice holder: 1 x crimp splice holder, 1 x heat-shrink splice holder
- Mounting compatibility: Suitable for standard 19" patch panels and fiber optic distribution boxes
- Color: White
- Cassette material: High-quality plastic
- Dimensions (L x W x H): 155 x 90 x 10 mm
- Weight: 52 g
- Operating temperature: -20 °C to +60 °C

#### Package contents

- 1 x fiber optic splice cassette with cover
- 1 x crimp splice holder, 1 x heat-shrink splice holder

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	250	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	135.00

More images:

