

# DIGITUS® M.2 NVMe + M.2 SATA SSD docking station with SD Express card reader, USB-C™

DA-71546-1

EAN 4016032501398



## Dual Bay Nvme+SATA 2-in-1 SSD Docking Station 2 bay SATA/NVME 2-in-1 Docking Station

The 3-in-1 docking station from DIGITUS® can accommodate M.2 SSDs in NVMe or SATA technology, and there is also an SD Express 7.1 card reader with the highest data transfer rates on board. Manage M.2 data carriers with up to 4 TB per slot and additional SD cards up to 2 TB. NVMe SSDs with B+M key & M key as well as SATA SSDs with B+M key, each in the formats 2242, 2260, 2280 & 22110 are supported. Easily expand the storage capacity of numerous USB-C™ devices such as PCs, notebooks, TVs, game consoles or routers.

### Manage M.2 NVMe and M.2 SATA SSDs via a USB-C™ connection - incl. integrated SD Express card reader

- 1 x M.2 bay for NVMe SSDs (B+M-Key / M-Key) 1 x M.2 bay for SATA SSDs (B+M-Key)

- Capacity: max. 4 TB per bay
- 1 x SD-Express 7.1 memory card reader 2 TB max. / 1000 MB/s max.
- Supported formats: 2242, 2260, 2280 & 22110
- USB-C™ connections: 1 x data USB-C™ 3.2 Gen2, 1 x
- Power supply USB-C™ socket
- Downwards compatible with USB 3.0 / USB 2.0
- Maximum transfer rate USB-C™: 10 Gbps
- Supports U.A.S.P. and T.R.I.M.
- Supports hot swap (insertion and ejection during operation)
- LED indicators for hard disk transfer (white), SD transfer (blue) & power (green)
- Areas of application: PC, notebook, TV, router or game consoles (with USB-C™ connection)
- Storage formats: NTFS, FAT, FAT32 Input voltage USB power supply: 100 -240 V AC, 50/60 Hz,

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	20	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	108.37

More images:

