

# DIGITUS® Socket strip with aluminum profile and back-up fuse, 9-way socket outlet with earthing contact, 2 m supply cable IEC C14 plug

DN-95437

EAN 4016032501640



### 1U Alu PDU, rackmount., 9x CEE 7/7 outlet, 1x outlet 10A Plug, 250VAC 50/60Hz, IEC C14 plug, pre-fuse

The DIGITUS® power strips are the perfect solution for your 482.6 mm (19") network or server cabinet. Optimized for cabinet mounting, the DIGITUS® power strips with 220-240V at 50-60 Hz offer you the best performance with a suitable load. The 482.6 mm (19") mounting material supplied ensures optimum attachment to the profile rails of your cabinets. Each socket strip can be mounted horizontally or vertically and, depending on the cabinet type, it is possible to mount the socket strip with the taps facing upwards or downwards.

#### Safe and professional power supply in the 482.6 mm (19") range

- 9x socket outlets with earthing contact 250VAC 50/60Hz / 10A / 2500W
- Aluminum profile

- 2x angle profiles for cabinet assembly
- 2 m supply cable H05VV-F 35 1.5 mm<sup>2</sup> with IEC C14 plug
- Plastic components made of ABS UL-94V-0
- Earthing on the aluminum profile
- Sockets with earthing contact rotated by 45
- Back-up fuse
- Rated voltage: 230-250 VAC, 50/60 Hz

#### Attributes

- Current: 10 A
- Input Plug: IEC 60320 C14 inlet
- Installation: Rack 1U
- Outlets: CEE 7/3
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

