

DIGITUS® Solar cable extension 3 m, 4 mm², MC4 connection, PV cable 1500 V DC, UV-resistant & weatherproof, 2 cables, 1x black, 1x red

DK-SCEC64-0030

EAN 4016032501831



Solar Extension cable, 4 sqmm, MC4 connector 3m,4sqmm,halogen-free,UV-res.,flex,IP67,2pcs

This high-quality solar cable for extension with pre-assembled MC4 connectors at both ends has been specially developed for use in photovoltaic systems. With a conductor cross-section of 4 mm², a length of 3 m and a dielectric strength of up to 1500 V DC, it is ideal for connecting solar modules, inverters or other PV components. The cable consists of a tinned copper conductor, which ensures optimum current transmission and reliable corrosion protection. The resistant XLPO insulation and robust PA66 jacket offer excellent protection against UV radiation, moisture, ozone and mechanical stress. Thanks to the pre-assembled MC4 connections, the cable is ready for immediate use and can be installed effortlessly - ideal for DIY solar projects or professional PV installations. With an operating temperature range of -40°C to +85°C, flame-retardant properties (UL94 V-0) and a contact resistance of 0.509mΩ, this cable guarantees maximum safety, efficiency and durability - even in demanding weather conditions.

Safe, efficient and ready to use - this solar cable extension with MC4 connections is the perfect plug-and-play solution for all indoor and outdoor photovoltaic projects.

- Length: 3m
- Conductor cross-section: 4mm²

- Voltage tolerance: up to 1500V DC / 1000V AC
- Rated current: 30 A
- Conductor material: Tinned copper wire
- Conductor structure: TS 56/0.285±0.01
- Conductor diameter: 2.4mm
- Insulation material: XLPO
- Jacket material: XLPO
- Plug material: PPE, PA 66, halogen-free
- Insulation diameter: 3.8mm ±0.1mm
- Outer diameter: 5.5mm ±0.2mm
- Temperature range: -40 °C to +85 °C
- Contact resistance: 0.509mΩ
- Insulation resistance: 580MΩ-km
- Dielectric strength: AC 6.5 kV / DC 15 kV (5 minutes)
- Spark test: 7 kV
- Standards & certificates: CEEN 50618, EN 60332-1-2 (Eca) , EN 62852: 2015, UL94 V-0
- Coat color: 1x black, 1x red
- Connection 1: MC4 plug
- Connection 2: MC4 socket

Package contents

- Pair of 2 solar cables, 1x black, 1x red

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	16.30	50.00	28.00	28.00	39,200.00
Packaging Unit Inside	1	0.41	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.41	28.50	18.50	4.50	2,372,620.00
Net single without Packaging	0	0.39	19.00	19.00	5.00	1,805.00

More images:



Solar Extension Cable

MC4 connector
3.5m, 4mm²

25 years long life

Security lock

Waterproof sealing ring

PPE insulation

UV resistant

Waterproof

Temperature resistant (-40 to +85 degree)

Flexible & easy to install

DIGITUS

MC4 solar connector

Flexible & easy to install

PPE insulation

IP65 & IP68 waterproof

Safety-Lock design

The MC4 connectors are easy to connect. The sophisticated product design (safety-lock design) prevents the connectors from accidentally coming loose.

Product parameter

Product name	Solar extension cable
Cable specifications	1/3" x 1/3" 15m 6mm ² 3.5m 4mm ²
Connector	MC4 connector / PAB0
Rated current	30A
Rated voltage	DC 1500V
Insulation material	XLPO
Weather resistance	UV
Insulation resistance	> 500 MΩ·km
Contact resistance	< 5mΩ
Temperature range	-40°C to +85°C
Waterproof level	IP65 & IP68
Life time	25 years

Versatile in use

- ✓ Flame retardant according to EN 50618:2014
Increased safety for PV systems
- ✓ DC 1500V voltage
Perfect for high power requirements in PV systems
- ✓ Long service life of up to 25 years
Designed for maximum durability and efficiency

Safe, efficient and ready to use

This solar cable extension with MC4 connections is the perfect plug-and-play solution for all indoor and outdoor photovoltaic projects.

1-15m, 4mm²/6mm² copper conductor, tin-plated
For maximum conductivity and corrosion protection

CE and EN 50618, EN 60332-1-2 (Eca)
EN 62852:2015 certified
Approved for international use

MC4 connector pre-assembled
Can be connected quickly, safely and without tools

Ideal for photovoltaic & solar systems