

# DIGITUS® Fiber optic crimp splice protection, 15 strips, with telecom approval TS0338/96

DN-CSP-015

EAN 4016032504955



### Fiber Optic Crimp Splice Protection 1 Tray with 15 pcs

The fiber optic crimp splice protector offers a safe way to reliably protect optical fibers after splicing. It is fixed in place purely mechanically by means of a precise crimping process. Thanks to its compact design, the crimp splice protector is perfect for splice cassettes and distributors with limited space. The 900 µm secondary coating of the fiber is held firmly in place, permanently protecting the sensitive splice against tension, vibrations and micromovements. The easy handling makes the crimp splice protector the ideal solution for field installations, e.g. in building cabling, FTTH installations or data centers. They are used to protect fiber splices in 19" distribution panels, floor-standing and wall-mounted enclosures as well as in fiber optic splice closures. Thanks to their excellent climatic and thermal properties, they are suitable for use in both closed and open environments. The protection thus ensures permanent

resistance to crushing, pulling and puncturing.

### Efficient splice protection for optical fibers with crimp technology. Compatible with standard splice cassettes, ideal for compact installations.

- Compliant with TS 0388/96
- Fixation: Mechanical clamp fastener
- Fastening: Snap-in or insertable in standard splice cassettes
- Damping behavior: No additional insertion loss
- Dimensions (LxWxH) : 30 mm × 1.2 mm × 3.3 mm
- Opening angle of the protector before crimping:  $\alpha=52^\circ$
- Temperature range: -20 °C to +60 °C

### Package contents

- 1x fiber optic crimp splice protection, strip of 15

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	0	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	0	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

