

Planet 16-Port 10/100/1000T 802.3at PoE + 2-Port Gigabit SFP Ethernet Switch with LCD PoE Monitor (300W)

GSW-2620VHP
EAN 4711605282109



Planet 19 Inch POE+ Switch with LCD, 802.3at, 24xRJ45 Gigabit, 2xSFP, VLAN, 300W + 2-Port Gigabit SFP and LCD Monitor for PoE,

26 port Gigabit Ethernet Switch 19 Inch 1U with display for quick monitoring of helpful status information. 24 x 10/100/1000 (RJ45) with PoE+ 802.3at Injector, compatible with 802.3af, 2 x SFP Slots 100/1000 Mbps, PoE Power Budget 300 Watt. Port-based VLAN (isolation) can be activated/deactivated via a DIP switch, as well as a special PoE mode that allows a range of 250 meters (with 10 Mbps) instead of only 100 meters (with 1000 Mbps). Power consumption max. 330 watts. Including 19 inch mounting bracket. Weight 3.4kg, dimensions 233 x 440 x 44 mm.

LCD Monitor for Real-time PoE Usage and System Status Display

- Hardware-based 10/100/1000Mbps auto-negotiation and auto MDI/MDI-X
- Flow control for full duplex operation and back pressure for half duplex operation
- 9216bytes packet size
- Integrates address look-up engine, supporting 8K absolute MAC addresses
- IEEE 802.1Q VLAN transparency
- Automatic address learning and address aging
- 19-inch desktop size, 1U height, rack mountable
- LED indicators for system power, per port PoE ready and PoE activity, speed, Link/Act
- 3 silent fans to provide stable and efficient power performance
- Supports Energy-Efficient Ethernet (EEE) function (IEEE 802.3az)
- Supports contact discharge of ± 6 KV DC and air discharge of ± 8 KV DC for Ethernet ESD protection
- Supports ± 6 KV surge immunity
- PoE Standard: IEEE 802.3af Power over Ethernet/PSE, IEEE 802.3at Power over Ethernet Plus/PSE

- PoE Power Output: Per port 53V-54V DC, 300mA. max. 15.4 watts (IEEE 802.3af), Per port 53V-54V DC, 600mA. max. 30 watts (IEEE 802.3at)
- Power Pin Assignment: 1/2 (+), 3/6 (-)
- PoE Power Budget: 300 watts
- Max. Number of Class 2 PDs: 24
- Max. Number of Class 3 PDs : 23
- Max. Number of Class 4 PDs: 11
- Operating Temperature: -10 ~ 60 degrees C
- Storage Temperature: -10 ~ 70 degrees C

Attributes

- Number of ports: 24
- PoE Power budget: 300 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Power output: 24 W
- Industrial usage: no
- Installation type: 19 inch
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vanadism: no
- Uplink port connection: SFP
- VLAN: yes

Package contents

- 24 Port PoE Switch GSW-2620VHP
- Power Cable
- Installation Material
- Manual

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	3.40	44.00	23.30	4.40	4,510.88