

# DIGITUS® CAT 6, modular couplers, shielded

AT-AG 8/8 C6S

EAN 4016032229032



### Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0

- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

#### Attributes

- Category: CAT 6

| Logistics                    |              |             |            |            |             |       |
|------------------------------|--------------|-------------|------------|------------|-------------|-------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³   |
| Packaging Unit Carton        | 500          | 9.80        | 54.00      | 35.00      | 12.00       | 22.68 |
| Packaging Unit Inside        | 50           | 0.98        | 22.00      | 20.00      | 6.00        | 2.64  |
| Packaging Unit Single        | 1            | 0.02        | 4.00       | 2.00       | 2.00        | 16.00 |
| Net single without Packaging | 0            | 0.03        | 0.00       | 0.00       | 0.00        | 0.00  |

### Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)