

DIGITUS® Wallplate for Keystone Modules, Frame 80x80mm, French type

DN-93802

EAN 4016032259350



Faceplate for Keystone Jacks, 2x RJ45, dust cover 80x80 mm + 2x 22.5 mm modular insert, RAL 9003

The DIGITUS® Faceplates are suitable for the connection of all DIGITUS® Keystone Modules. Included dust protection shutters provide a perfect protection. Their connection way of the module is 45° vertical (German and British Layout) or 90° horizontal (French Layout).

- Layout keystone entry: 90° outlet
- Area of application: Cavity socket, trunking, surface mount box
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for installation in trunking, flush and surface mount

- Integrated dust cover
- Plastic label field
- Design compatible to current switch ranges of switch manufacturers
- Technical properties:
- Wall outlet material: Thermoplast, ABS UL 94V-0
- Central plate material: ABS UL 94V-0
- Frame material: ABS UL 94V-0
- Surface mount box material: ABS UL 94V-0
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	17.30	41.00	39.00	29.00	46.37
Packaging Unit Inside	1	0.06	1.50	16.00	10.00	240.00
Packaging Unit Single	1	0.06	1.50	16.00	10.00	240.00
Net single without Packaging	0	0.05	1.50	8.50	8.50	108.38

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>

info@assmann.com