

# DIGITUS® Modular patch panel, 24-port

DN-91411

EAN 4016032280798



## Modular Patch Panel, shielded 24-port, blank, 1U, rack mount, black RAL 9005

The modular patch panel from DIGITUS® is available as a 16- or 24-port version. The 1.5 mm cold-rolled carbon steel provides optimum support for your Keystone modules.

- Keystone mount version: Straight
- Application areas: 483 mm (19") distribution cabinet
- Standards: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C.2
- General properties:
- Suitable for 483 mm (19") rack mounting
- Suitable for shielded Digitus® Keystone modules and connectors
- Central earthing connection
- Technical features:

- Housing material: 1.5 mm SPCC cold-rolled sheet steel, powder-coated
- Material standard: EN 10 130(1991), BS 1449, NFA 36/401, DIN 1623, UNI 5866, UNE 36-086, SIS, JIS G 3141, ASTM, SAE, NFA 36/401
- Material earthing bar: galvanized steel
- Physical properties:
- Operating temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Color: Black RAL9005


### Attributes

- Boja: crna, RAL 9005
- Jedinice: 1
- Priključci: 24

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	15	13.10	57.00	52.00	26.00	77.06
Packaging Unit Inside	1	0.87	7.50	56.00	10.00	4.20
Packaging Unit Single	1	0.87	7.50	56.00	10.00	4.20
Net single without Packaging	0	0.42	0.90	48.20	4.40	190.87

**More images:**



**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)