

DIGITUS USB 2.0 connection cable, USB A to USB B

DB-300105-030-S EAN 4016032284222





USB 2.0 connection cable, type A - B M/M, 3.0m, USB 2.0 conform,

This cable is suitable for connecting USB devices with a USB B jack. For example, you can operate printers, external hard drives or other peripheral equipment with a USB B jack to a USB port (PC, notebook or USB hub). Thanks to USB 2.0 compatibility, the transmission rate is up to 480 Mbps (Hi-Speed). The sturdy cable is double-shielded, which contributes to optimal data transmission.

Use external devices with a USB B connection - Compatible with USB 2.0 Hi-Speed data transmission $\,$

Attributes

- Feritni filtar: nema
- · Kabel u boji: crni
- Konektor 1: Micro USB B, utikač
- Konektor 2: USB A, utikač
- Površina konektora: poniklanoUSB sukladnost: USB 2,0
- Duljina: 3 m

| Logistics | | | | | | |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 40 | 12.30 | 37.00 | 11.50 | 29.00 | 0.00 |
| Packaging Unit Inside | 10 | 3,075.00 | 37.00 | 11.50 | 29.00 | 0.00 |
| Packaging Unit Single | 1 | 0.31 | 5.00 | 10.00 | 25.50 | 1,275.00 |
| Net single without Packaging | 0 | 0.00 | 2.00 | 12.00 | 14.00 | 336.00 |

More images:











Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
 operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

 $\ensuremath{\mathsf{EU}}$ based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com